

## 3Com® 3100 Entry Phone

### DATA SHEET



#### Key Features

- Outstanding value
- Four fixed-feature buttons
- Wideband audio ready
- Large message-waiting LED
- One 10/100 uplink port
- Power over Ethernet support (802.3af)

#### Ideal Uses

- Manufacturing floors
- Office lobbies
- Visitors' workspaces
- Warehouses
- Other common areas

### PRODUCT SUMMARY

The 3Com® 3100 Entry Phone with its exceptional affordability, outstanding audio quality, compact form factor, and easy operation offers organizations a perfect solution for common areas and other business environments that require a simple connection to the IP telephony system. Designed as a cost effective replacement to a traditional analog phone, the 3100 model can utilize a standard ethernet connection—no separate voice cable run is needed.

Sharp acoustics and ergonomics-inspired design encourage collaboration and increased productivity. Self-locating capabilities save time and service-call expenses, lowering total cost of ownership. Moving a phone involves simply plugging it into a network port at a new location. All personal settings, directory entries, and voice mail travels with the phone.

Browser-based management eases configuration tasks, and web-based support makes advanced features easier to master. What's more, customization capabilities let users do many set-up procedures themselves.

## Ordering Information

PRODUCT DESCRIPTION	3COM SKU
3Com 3100 Entry Phone	3C10399A

### 3COM IP PHONES PORTFOLIO AT A GLANCE



	3100 Entry Phone	3101 Basic Phone	3101 Basic Phone with Speaker	3102 Business Phone	3103 Manager Phone	3105 Attendant Console	3106 Cordless Phone	3107 Cordless Phone
Maximum system (line) appearances	1	4	4	18	12	50	4	4
Programmable buttons with lights	No	4	4	18	8	50 / 100 with Shift Button	4	4
Fixed feature buttons	4	5	6	10	10	4	8	9
Display softkeys	No	3	3	3	10	No	No	No
Four-way cursor control	No	Yes	Yes	Yes	Yes	No	No	No
Display size	No	160 x 33 pixels	160 x 33 pixels	160 x 33 pixels	320 x 120 pixels	No	2 lines	2 lines
Ethernet ports	1 - 10/100	2 - 10/100	2 - 10/100	2 - 10/100	2 - 10/100/1000 (Gigabit)	1 - 10/100	1 - 10/100	1 - 10/100
Power over Ethernet support (802.3af)	Yes	Yes	Yes	Yes	Yes	Yes	No	No
Speakerphone	No	Listen-only	Half duplex	Full duplex	Full duplex	No	No	No
Wideband audio support	Handset only	Handset only	Handset only	Yes	Yes	No	No	No
Definable ring tones	No	9	9	9	9	No	No	No
Headset jack	No	No	No	Yes	Yes	No	Yes	Yes
Codecs G.711, ADPCM, G729 A/B	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes
G.722 codec-ready handset	Yes	Yes	Yes	Yes	Yes	No	No	No
G.722 codec-ready speakerphone	No	No	No	Yes	Yes	No	No	No
Adaptive jitter buffer	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes
QoS: IP-ToS, 802.1p	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes
TAPI support	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
DHCP, Option 184	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Desk or wall mountable	Yes	Yes	Yes	Yes	Yes	Yes	Yes - base unit	Yes - base unit
Removable faceplate for localization	No	No	No	Yes	Yes	No	No	No
Browser-based administration	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Platform support	NBX, VCX*	NBX, VCX	NBX, VCX	NBX, VCX	NBX, VCX*	NBX, VCX	NBX only	NBX only

\*Implementation of VCX (SIP-based) support expected summer, 2005.



3Com Corporation, Corporate Headquarters, 350 Campus Drive, Marlborough, MA 01752-3064

To learn more about 3Com solutions, visit [www.3com.com](http://www.3com.com). 3Com is publicly traded on NASDAQ under the symbol COMS.

Copyright © 2005 3Com Corporation. All rights reserved. 3Com, the 3Com logo, and NBX are registered trademarks of 3Com Corporation. Exercise Choice and VCX are trademarks of 3Com Corporation. All other company and product names may be trademarks of their respective companies. While every effort is made to ensure the information given is accurate, 3Com does not accept liability for any errors or mistakes which may arise. Specifications and other information in this document may be subject to change without notice.