

3Com® 3105 Attendant Console

DATA SHEET



Key Features

- 50 programmable keys with LEDs
- 100 functions available by toggling Shift key
- Four preprogrammed feature keys
- Direct Station Selection and Busy Lamp Field (DSS/BLF) functions
- Concurrent use of multiple consoles
- 10/100 uplink port
- Power over Ethernet support (802.3af)

Ideal for

- Phone attendants
- Receptionists
- Workgroup administrators

PRODUCT SUMMARY

The 3Com® 3105 Attendant Console helps organizations make a good first impression by providing attendants, receptionists, and other first-contact workers with a fast, intuitive way to handle inbound calls. Ergonomics-inspired design encourages collaboration and increased productivity. The console is equipped with 50 programmable buttons, each of which can invoke a second feature with a touch of the illuminated Shift key. Four additional buttons are reserved for frequently used features such as zone paging, call park, and transfer to voice mail.

When used with a 3Com Basic, Business, or Manager Phone, the console can indicate the phone status of up to 100 staff members, allowing the attendant to quickly and efficiently perform tasks such as transferring calls and accessing direct line appearances.

Multiple consoles may be connected in parallel to service larger locations. And an IEEE 802.3af Power over Ethernet capability provides location flexibility.

Self-locating capabilities save time and service-call expenses, lowering total cost of ownership. Moving a phone involves simply plugging it into a network port at a new location. All personal settings, directory entries, and voice mail travels with the phone.

Browser-based management eases configuration tasks, and web-based support makes advanced features easier to master. What's more, customization capabilities let users do many set-up procedures themselves.

Ordering Information

PRODUCT DESCRIPTION	3COM SKU
3Com 3105 Attendant Console	3C10405A

3COM IP PHONES PORTFOLIO AT A GLANCE



Maximum system (line) appearances	1	4	4	18	12	50	4	4
Programmable buttons with lights	No	4	4	18	8	50 / 100 with Shift Button	4	4
Fixed feature buttons	4	5	6	10	10	4	8	9
Display softkeys	No	3	3	3	10	No	No	No
Four-way cursor control	No	Yes	Yes	Yes	Yes	No	No	No
Display size	No	160 x 33 pixels	160 x 33 pixels	160 x 33 pixels	320 x 120 pixels	No	2 lines	2 lines
Ethernet ports	1 - 10/100	2 - 10/100	2 - 10/100	2 - 10/100	2 - 10/100/1000 (Gigabit)	1 - 10/100	1 - 10/100	1 - 10/100
Power over Ethernet support (802.3af)	Yes	Yes	Yes	Yes	Yes	Yes	No	No
Speakerphone	No	Listen-only	Half duplex	Full duplex	Full duplex	No	No	No
Wideband audio support	Handset only	Handset only	Handset only	Yes	Yes	No	No	No
Definable ring tones	No	9	9	9	9	No	No	No
Headset jack	No	No	No	Yes	Yes	No	Yes	Yes
Codecs G.711, ADPCM, G729 A/B	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes
G.722 codec-ready handset	Yes	Yes	Yes	Yes	Yes	No	No	No
G.722 codec-ready speakerphone	No	No	No	Yes	Yes	No	No	No
Adaptive jitter buffer	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes
QoS: IP-ToS, 802.1p	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes
TAPI support	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
DHCP, Option 184	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Desk or wall mountable	Yes	Yes	Yes	Yes	Yes	Yes	Yes - base unit	Yes - base unit
Removable faceplate for localization	No	No	No	Yes	Yes	No	No	No
Browser-based administration	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Platform support	NBX, VCX*	NBX, VCX	NBX, VCX	NBX, VCX	NBX, VCX*	NBX, VCX	NBX only	NBX only

*Implementation of VCX (SIP-based) support expected summer, 2005.



3Com Corporation, Corporate Headquarters, 350 Campus Drive, Marlborough, MA 01752-3064

To learn more about 3Com solutions, visit www.3com.com. 3Com is publicly traded on NASDAQ under the symbol COMS.

Copyright © 2005 3Com Corporation. All rights reserved. 3Com, the 3Com logo, and NBX are registered trademarks of 3Com Corporation. Exercise Choice and VCX are trademarks of 3Com Corporation. All other company and product names may be trademarks of their respective companies. While every effort is made to ensure the information given is accurate, 3Com does not accept liability for any errors or mistakes which may arise. Specifications and other information in this document may be subject to change without notice.