

Economical, standards-based IP telephony platform with a range of built-in applications, full feature-set and direct connection to BRI trunking

OVERVIEW

The 3Com® NBX® V3000 BRI-ST platform is a full-featured IP telephony solution designed for small- and medium-sized organizations moving to a Voice over Internet Protocol (VoIP) architecture. Its ease of use allows non-technical personnel to make individual or system-wide changes with the click of a mouse. The system's ability to scale up to 1,500 devices and to support standards-based protocols, including Session Initiation Protocol (SIP), gives organizations the confidence to choose the NBX solution for their current and future telecom needs.

With a built-in BRI gateway interface that can reduce configuration time and its related costs, the platform allows direct connection to the Public Switched Telephone Network (PSTN) of up to four lines (eight channels) of BRI-ST central office (CO) trunking. Additionally, the V3000 BRI-ST platform—in combination with an NBX Expansion Chassis—accommodates further communications options via T1/E1, PRI, analog and BRI digital trunking.

To increase productivity and reduce operating costs, the solution also features a host of integrated applications, including voice messaging that provides a voice mailbox with auto-setup for every user, call center software that enhances the efficiency of agents in a queue, as well as easy to set-up hunt groups, auto-attendant, supervisory monitoring and call reporting. Email integration, supported on any IMAP4-compliant email system, offers the ability to share a common inbox for email and voice messages. Plus, V3000 BRI-ST solutions let organizations centrally manage IP telephony services using the 3Com NBX NetSet™ web-based management utility.

KEY BENEFITS

PROTECT INVESTMENTS WITH MULTIPLE PROTOCOL SUPPORT

NBX V3000 BRI-ST platforms with R6.0 and higher system software can operate in either of two modes: Standard NBX or SIP mode. **Standard NBX mode** utilizes the traditional protocol on which six generations of 3Com NBX applications have been built since 1998, while **SIP mode** allows the NBX to communicate with third-party SIP-compliant devices and applications. 3Com's goal of ensuring its customers access to continuously evolving telecom standards, maximizes functionality and the return on investment (ROI) from NBX solutions.

ENABLE BUSINESS APPLICATIONS WITH SIP

SIP support unlocks access to advanced applications that optimize the productivity-enhancing benefits of Voice over IP (VoIP) technology and facilitates employee communications with collaborative tools such as IP Messaging and IP Conferencing applications.



Standards-based 3Com V3000 BRI-ST platforms offer a comprehensive set of features, all in a compact form factor for particularly cost-effective and practical deployment.

KEY BENEFITS (CONTINUED)

INCREASE PRODUCTIVITY WITH BUILT-IN NBX AUTOMATIC CALL DISTRIBUTION (ACD)

Call center hotline, help desk and telesales staff work more efficiently with NBX ACD software included in the V3000 BRI-ST platform. Two agent licenses are packaged with each platform and additional licenses are available with key-code activation. Supervisors obtain real-time, up-to-the-minute vital statistics on call center performance via voice monitoring or on their computer screens with PC-based software.

EASE IP TELEPHONY IMPLEMENTATION

Standards-based design, including support for switched IEEE 802.3af Power over Ethernet (PoE), facilitates seamless integration with existing network infrastructure. The web-based NBX NetSet management utility, hosted by the NBX platform, provides intuitive system configuration that lets organizations avoid the need to train personnel in using command line interfaces or new programming languages.

The screenshot displays the 'System Identity' configuration page for an NBX V3000 system. The left sidebar contains a navigation menu with categories like System-Wide Settings, Feature Settings, System Maintenance, Telephone Configuration, User Configuration, Call Distribution Groups, PSTN Gateway Configuration, NBX Messaging, SIP Applications, Dial Plan, Virtual Connections, Downloads, Licensing and Upgrades, Reports, Network Management, and Country Settings. The main content area shows the following system details:

Software Version:	X6_0_18
System Serial #:	0752200400
Host Name:	V3000
IP Address:	192.168.1.190
Default Gateway:	0.0.0.0
Subnet Mask:	255.255.255.0
Network Protocol:	Ethernet Only
MOH MAC Address:	00:e0:bb:1d:7c:ab
Free Memory (in bytes):	32,245,832
Memory Upgrade Installed:	NO (117,436,416 byte)
Date and Time:	Tuesday, December 6, 2005, 12:52:39 PM
System Start Time:	Monday, December 5, 2005, 4:12:45 PM

At the bottom left, the footer indicates: NBX® Version X6_0_18, Copyright © 2005, 3Com® Corporation, All Rights Reserved.

The NBX NetSet management interface provides point-and-click setup for the most basic or the most complex telephony features.

MATCH IP PHONE CHOICES TO ANY APPLICATION AND BUDGET

To optimize infrastructure investments, 3Com gives organizations a range of IP phone choices, all with robust feature-sets. Communications options include 10/100/1000 Mbps Ethernet/IP phones, softphones, receptionist consoles and cordless phones that run in either standard NBX or SIP call control mode. Where secure connectivity needs to be maintained while roaming through a business location, 3Com also offers the SIP-based 3108 Wireless Phone, an 802.11b/g-compliant wireless handset in a flip-phone form factor.

COST-EFFECTIVELY EXPAND TO MEET EVOLVING NEEDS

Organizations can boost capacity or add functionality with practical key-coded software upgrades that let them align their needs and budget. With cost-saving incremental licensing, they can scale their NBX system up to 1,500 devices (lines/stations; maximum of 720 PSTN lines).

CREATE A SEAMLESS MULTISITE VOICE NETWORK

NBX V3000 BRI-ST solutions connect not only branch sites to corporate offices, but also remote and home office workers to their main office convergence services.

FEATURE HIGHLIGHTS

- › Support for traditional voice and multimedia communications
- › Embedded applications including voice messaging, auto-attendant, and call center software
- › Interoperability with SIP-compliant devices, applications and endpoints
- › Browser-based NBX NetSet management tool to ease system setup and maintenance
- › Compliance with Section 508 of the United States Rehabilitation Act that regulates electronic and information technology accessibility for persons with disabilities
- › Management options that include SYSLOG, SNMP, SNTIP, NBX Multisite Backup Tool and NBX Dial Plan Editor
- › Inclusion of 15 phone licenses with base system purchase
- › Multilingual NBX NetSet end-user support for United States English, Latin American Spanish, Brazilian Portuguese and Italian

SPECIFICATIONS

PLATFORM

Can operate in either Standard mode using the NBX call control protocol or in SIP mode with NBX R6.0 or higher software

SYSTEM REQUIREMENTS

100BASE-TX or switched Ethernet LAN
3Com NBX V3000 Analog platform
Minimum of two 3Com IP phones

SYSTEM CAPACITY

Support for up to 1,500 devices (lines/stations), including up to 720 PSTN CO lines and 48 Virtual Tie Lines (NBX Standard mode) or up to 300 SIP trunks (NBX SIP mode with R6.0 or higher software)

PSTN GATEWAY OPTIONS

Loop-start analog, T1/PRI, E1/PRI, ISDN BRI-ST, Q.SIG/PRI

Support for SIP analog and digital gateways in SIP mode with NBX R6.0 or higher software

PORT CONNECTIONS

WAN: via external router with IP-ToS support

LAN: dual, redundant LAN 10/100 uplink ports

ANALOG DEVICES

Support for 2500 series-compatible analog devices, including cordless phones, fax machines, night bells and door ringers; two FXS ports included on a V3000 platform with optional support for additional analog devices via the NBX Expansion Chassis and Analog Station card

NETWORK, PRIORITIZATION AND AUDIO COMPRESSION STANDARDS

H.323, G.711, G.729a/b, ADPCM, G.722, 802.1d, 802.1p, 802.1q, 802.2, 802.3af, 802.11, IP, IP-ToS, DiffServ, TCP/IP, UDP/IP, DHCP, DNS

APPLICATION STANDARDS

SIP, TAPI 2.1, TAPI/WAV, IMAP4, HTTP, H.323, SMTP/MIME, VPIM

MANAGEMENT

Built-in 3Com NBX NetSet utility;
3Com Network Supervisor support

NBX VOICEMAIL LANGUAGES/ DIALECTS

Chinese (Cantonese), Chinese (Mandarin), English (Australian), English (United Kingdom), English (United States), French (Parisian), German, Hebrew, Italian, Spanish (Castilian), Spanish (Latin American), Russian

POWER REQUIREMENTS

NBX V3000 BRI-ST platform: 100-120 VAC, 50-60 Hz, 1A
220-240 VAC, 50-60 Hz, 0.5A

POWER DISSIPATION

NBX V3000 BRI-ST platform: 50 W
IP Phones: 8 W (maximum)

CHASSIS/CALL PROCESSOR DIMENSIONS AND WEIGHT

Height: 4.445 cm (1.75 in)
Width: 48.815 cm (17.25 in)
Depth: 37.465 cm (14.75 in)
Weight: 5.68805 kg (11.54 lb)

ENVIRONMENTAL RANGES

Operating temperature: 0° to 40°C (32° to 104°F)
Storage temperature: -40° to +70°C (-40° to +158°F)
Humidity: 5 to 85% noncondensing

NETWORK ACCESS STANDARDS

National Requirements FCC Part 68 (United States), CS03 (Canada), CTR4/A1 Commission Decision 98/520 (European Community)

SAFETY

UL/CUL 1950 Third Edition
IEC 60950: 1991 + A1, A2, A3, A4;
National deviations for Europe and Australia

EMISSIONS

FCC Part 15 Class A and B
EN 55022: 1994/A1, 1995/A2, 1997/Class A
VCCI Class A
AS/NZS 3548: 1995/Class A
RoHS-compliant

IMMUNITY

EN 55024: 1998

**ORDERING
INFORMATION**

PRODUCT DESCRIPTION	3COM SKU
NBX V3000 BRI-ST Platform R6.0	3C10601A
NBX V3000 BRI-ST 2-port to 4-port Upgrade	3C10166
NBX V3000 512 MB Memory Upgrade Kit (required for more than 250 device licenses and/or to enable SIP)	3C10240

3Com authorized partners can access design tools and voice-specific services which will deliver an optimal solution to meet any enterprise communications requirements.

Preliminary quotes using a simplified set of user-defined requirements can be obtained using the web-based 3Com Voice Solution Finder tool at www.3com.com/voipfinder.

Visit www.3com.com/voip for more information about 3Com secure converged network solutions.

3Com Corporation, Corporate Headquarters, 350 Campus Drive, Marlborough, MA 01752-3064
3Com is publicly traded on NASDAQ under the symbol COMS.

Copyright © 2007 3Com Corporation. All rights reserved. 3Com, the 3Com logo and NBX are registered trademarks of 3Com Corporation. NBX NetSet is a trademark of 3Com Corporation. All other company and product names may be trademarks of their respective companies. While every effort is made to ensure the information given is accurate, 3Com does not accept liability for any errors or mistakes which may arise. All specifications are subject to change without notice.

